

Fu Yang Technology



OIL WATER SEPTARATOR PROFESSIONAL MACHINE MANUFACTURING

Company Introduction

Fu Yang Technology Co., Ltd. is always in the two concepts “green “and” saving” and professional skills in manufacturing the products. We manage business seriously more than 20 years in wastewater treatment and wastewater recycling and other areas. We keep investing in a lot of projects, accumulating a wealth of experience, so our products have been sold around the world. Over the years, our excellent performance, high-quality support services, and a good reputation have gained the majority of customers trust for many years. Our professional skills and friendly service team is worth your trust definitely.

1



Benefits / Advantages

- ☆ **Specialized R&D Team**
- ☆ **Excellent Technical Group**
- ☆ **Precise Detective Instrument**
- ☆ **Material-Using Guarantee**
- ☆ **Easily to Install and Operate**
- ☆ **Assembling Any Workplaces**
- ☆ **Small, Space less**
- ☆ **Wonderful Price Competition**
- ☆ **Wholesome After-Sale Service**
- ☆ **Professional Problem-Solving Department**

Product Outline

Main models : Belt type oil skimmer

The small-volume oil skimmers are for removing floating oil, which can be connected on the machine tools directly showed below:

- CNC lathe
- Ships' bilges
- Steel industries
- Coolant systems
- Wastewater sumps
- Heat treating fluids
- Underground tanks
- Precisions industries
- Food processing plants
- Hydroelectric power plants
- NC(numerical control) machine tools
- Parking lots, garages, and service facilities
- Industrial machines (Drilling machine, Grinding machine, Mill machine)



The main role

- Increasing metalworking fluids, cleaning fluid cycle, so as to achieve the purpose of reducing operating costs.
- It can protect and improve the function of the efficiency of cleaning equipment.
- Saving environmental effects, to prevent indiscriminate discharge of waster oil pollution, in order to adapt the concept of environmental protection requirements.

Model : FY-601 Chain type oil skimmer



Specification

Chain belt: 65mm (width)


Degreasing amount: 0 to 20 liters/hr

Power: 110V/220V / 50Hz 60Hz/

Weight: about 9kg

Function

1. Increasing metalworking fluids, cleaning fluid cycle, so as to achieve the purpose of reducing operating costs.
2. It can protect and improve the function of the efficiency of cleaning equipment.
3. Saving environmental effects, to prevent indiscriminate discharge of waste oil pollution, in order to adapt the concept of environmental protection requirements.
- 4.



Customers provide the dimension **A** in order to decide the steel belt length for manufacture.

Model : FY-CNC-40 Belt type oil skimmer



Specification

Steel belt: 0.12*50mm (thickness*width)

Degreasing amount: 0 to 5 liters/hr


Power: 220V / 50Hz / 5W

Weight: about 3kg



Function

1. Increasing metalworking fluids, cleaning fluid cycle, so as to achieve the purpose of reducing operating costs.
2. It can protect and improve the function of the efficiency of cleaning equipment.
3. Saving environmental effects, to prevent indiscriminate discharge of waster oil pollution, in order to adapt the concept of environmental protection requirements.



Customers provide the dimension **A** in order to decide the steel belt length for manufacture.

Model : FY-300/400 Disc type oil skimmer


Specification

Specification of Suction plate: ϕ 300
Degreasing amount: 1.5 to 6 liters/ hour
Power: 220V/ 50Hz / 8W
Weight: 7.7 kg
Size (L*W*H): 251*330*315

Specification of Suction plate: ϕ 400
Degreasing amount: 3 to 15 liters/ hour
Power: 220V/ 50Hz / 25W
Weight: 10.6kg
Size (L*W*H): 251*430*420

Products Principle

The principle is to use the suction plate through by the motor to operate, when blowing across the surface with oil and draw away on the suction plate, than aggregate that to the oil trap. It can absorb the surface of oil slicks unceasingly by the motor rotate. It can remove surface oil slick clean. It can be used in a variety of machine tools and can use for a long time. It is conspicuous for more of the metal powder in the cutting fluid or more stable surface of the liquid in the sink.



Model : FY, Belt oil skimmer



Specification

JF-50


Steel belt width: 50mm
 Degreasing amount: 0 to 40 liters/ hour
 Power: 28W / 220V
 Weight: about 25 kg

JF-100

Steel belt width: 100mm
 Degreasing amount: 0 to 75 liters/ hour
 Power: 45W
 Weight: about 50 kg

Function

1. With a special oil-absorbing materials processing stainless steel, with a lipophilic hydrophobic properties, oil rate and fast.
2. The recovered oil is very low moisture content, can be used directly or refining reuse.
3. Using the temperature can exceed 120°C, can be used in high temperature environments acid and alkali.
4. Flexible design, according to the environmental requirements making use of the site or configure the strip length, and select standard or non-standard products. As the entire stainless steel, explosion proof, wind-based, anti-vapor type.
5. 24 hours, time proportional control.
6. Economical, low power consumption, without any supplies.



Customers provide the dimension **A** in order to decide the steel belt length for manufacture.

Model : FY-200 Belt oil skimmer




Specification

Steel belt width: 200mm
 Degreasing amount: 0 to 150 liters/ hour
 Power: 45W / 220V
 Weight: about 65 kg
 Material of steel belt: Special lipophilic stainless steel



Function

1. With a special oil-absorbing materials processing stainless steel, with a lipophilic hydrophobic properties, oil rate and fast.
2. The recovered oil is very low moisture content, can be used directly or refining reuse.
3. Using the temperature can exceed 120°C, can be used in high temperature environments acid and alkali.
4. Flexible design, according to the environmental requirements making use of the site or configure the strip length, and select standard or non-standard products. As the entire stainless steel, explosion proof, wind-based, anti-vapor type.
5. 24 hours, time proportional control.
6. Economical, low power consumption, without any supplies.



Customers provide the dimension **A** in order to decide the steel belt length for manufacture.

Model : FY-801 Floating ball skimmer



PNEUMATIC



Specification

Range of action: 5000mm
Degreasing amount: 0 to 360 liters/ hour
Power: 110V/220V/
Weight: about 30 kg
Material : SUS304
Temperature range : 5-70°C
PH range : $5 \leq \text{PH} \leq 11$
Power : Air Operated Double Diaphragm Pump



Features

1. Separate the waste oil effectively ,
2. Maintenance-free, No consumables , Reduce costs.
3. Separate purer oil with second separation tank.
4. Two filters:
First, there is stainless steel filter which can remove iron filings and other impurities.
Second, there are ten layer filters which can remove feather and shavings.



Model : FY-802 Floating ball skimmer



Specification

Range of action: 1000mm

Degreasing amount: 0 to 50 liters/ hour

Power: 110V/220V/

Weight: about 10 kg

Material : SUS304

Temperature range : 5-70°C


PH range : $5 \leq \text{PH} \leq 11$

Power : Electricity



Features

1. Separate purer oil with second separation tank.
2. Timer set.
3. Generate less bubble.



Model : FY-808 Floating ball skimmer



Specification


Range of action: 5000mm
Degreasing amount: 0 to 250 liters/ hour
Power: 110V/220V/
Weight: about 22 kg
Material : SUS304
Temperature range : 5-70°C
PH range : $5 \leq \text{PH} \leq 11$
Power : Electricity



Features

1. Separate the waste oil effectively ,
2. Maintenance-free, No consumables , Reduce costs.
3. Separate purer oil with second separation tank.
4. Two filters:

First, there is stainless steel filter which can remove iron filings and other impurities.
Second, there are five layer filters which can remove feather and shavings.





富揚科技有限公司
FuYang Technology Co., Ltd.



No.16-28, Zunwei Ln., Shetou Township, Changhua, Taiwan

Web : <http://www.getway-vegcutter.com>

E-mail : sales@getway-vegcutter.com

TEL: 886-4-8712073 (Taiwan)

FAX: 886-4-8730318(Taiwan)

